



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
| 10/735,417      | 12/12/2003  | Stephen C. Gordy     | 154363.204.2        | 2147             |

22913 7590 10/19/2007  
WORKMAN NYDEGGER  
60 EAST SOUTH TEMPLE  
1000 EAGLE GATE TOWER  
SALT LAKE CITY, UT 84111

|          |
|----------|
| EXAMINER |
|----------|

FRINK, JOHN MOORE

|          |              |
|----------|--------------|
| ART UNIT | PAPER NUMBER |
|----------|--------------|

2142

|           |               |
|-----------|---------------|
| MAIL DATE | DELIVERY MODE |
|-----------|---------------|

10/19/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

mn

|                              |                                      |                                     |  |
|------------------------------|--------------------------------------|-------------------------------------|--|
| <b>Office Action Summary</b> | <b>Application No.</b><br>10/735,417 | <b>Applicant(s)</b><br>GORDY ET AL. |  |
|                              | <b>Examiner</b><br>John M. Frink     | <b>Art Unit</b><br>2142             |  |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE \_\_\_\_ MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☐ Responsive to communication(s) filed on \_\_\_\_.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-33 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-33 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)            | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)   | Paper No(s)/Mail Date. ____.                                      |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date <u>7/19/2004</u> .   | 6) <input type="checkbox"/> Other: ____.                          |

## **DETAILED ACTION**

### ***Double Patenting***

1. Claims

- a. 1 of this application conflicts with claims 1, 5, 8 and 12
- b. 2 of this application conflicts with claim 1
- c. 3 of this application conflicts with claim 5
- d. 4 - 9 of this application conflict with claim 12
- e. 10 of this application conflicts with claim 11
- f. 11 of this application conflicts with claim 9
- g. 12 of this application conflicts with claim 10
- h. 13 of this application conflicts with claim 13
- i. 14 of this application conflicts with claim 14

of Application No. 10/735,8801. 37 CFR 1.78(b) provides that when two or more applications filed by the same applicant contain conflicting claims, elimination of such claims from all but one application may be required in the absence of good and sufficient reason for their retention during pendency in more than one application. Applicant is required to either cancel the conflicting claims from all but one application or maintain a clear line of demarcation between the applications. See MPEP § 822.

### ***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the

Art Unit: 2142

invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1 – 13, 15, 16, 17, 19 – 24, 26, 27, 29, 30 and 31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Worrall et al. (US 2006/0153177 A1), hereafter Worrall, in view of in view of Sørhaug et al. (US 6,424,627 B1), hereafter Sorhaug, further in view of Yanacek et al. (5,940,376), hereafter Yanacek.

4. Regarding claim 1, Worrall shows A network tap that permits an attached device to communicate with a node of a network, the node of the network communicating with a network cable transmitting network data thereon, the network cable having a first segment and a second segment, the network tap comprising: a first and second tap port, at least one of which is configured to receive a copy of network data obtained from the network cable, wherein the attached device can be selectively connected to at least one of the first and second tap ports (Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]).

Worrall does not show at least one of the first and second tap ports configured to receive device data from the attached device, the first and second tap ports being capable of operating in a plurality of modes, each being defined by enabling or disabling the ability of the first and second tap ports to receive network data and device data; means for inserting device data from the attached device into the network cable without disrupting the flow of data therein; and means for selecting one of the plurality of modes in which the first and second tap ports may operate.

Sorhaug shows at least one of the first and second tap ports configured to receive device data from the attached device, means for inserting device data from the

Art Unit: 2142

attached device into the network cable without disrupting the flow of data therein.

(Sorhaug, col. 2 lines 1 – 22, col. 2 lines 40 – 65, col. 3 lines 10 – 45).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall with that of Sorhaug in order to allow for more control of the network tap apparatus, and how the data in said network tap system was handled in order to enable more options for configuration and use as well as to monitor data at maximum data rates while providing not significant network data delay (Sorhaug, Abstract, col. 1 line 40 – col. 2 line 10).

Worrall in view of Sorhaug do not show the first and second tap ports being capable of operating in a plurality of modes, each being defined by enabling or disabling the ability of the first and second tap ports to receive network data and device data; and means for selecting one of the plurality of modes in which the first and second tap ports may operate.

Yanacek shows the first and second tap ports being capable of operating in a plurality of modes, each being defined by enabling or disabling the ability of the first and second tap ports to receive network data and device data; and means for selecting one of the plurality of modes in which the first and second tap ports may operate (Fig. 2, 10A – 10C).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall in view of Sorhaug and NetOptics with that of Yanacek in order to enable and more advanced and flexible system.

Art Unit: 2142

5. Regarding claim 2, Worrall in view of Sorhag and Yanacek further show wherein in one mode, the first and second tap ports are both enabled to receive the network data (Worrall, Figs. 1a-1c, 3a-3c; Sorhag, Fig. 2 and col. 2 lines 5 – 65).

6. Regarding claim 3, Worrall in view of Sorhag and Yanacek further show wherein in one mode, at least one of the first and second tap ports are enabled to receive device data (Worrall, Figs. 1a-1c, 3a-3c; Sorhag, Fig. 2 and col. 2 lines 5 – 65).

7. Regarding claims 4 - 9, Worrall in view of Sorhag and Yanacek further show wherein the first and second tap ports are capable of operating in a plurality of modes, each mode being defined by enabling or disabling the ability of the first and second tap ports to receive data (Yanacek Fig. 2, 10A – 10C), including network and device data (Worrall, Figs. 1a-1c, 3a-3c; Sorhag, Fig. 2 and col. 2 lines 5 – 65).

Worrall in view of Sorhag and Yanacek thus disclose enabling or disabling the ability for each of the tap ports to receive network and device data.

It would have been obvious to one of ordinary skill in the art at the time of the invention to experiment and try the various permutations of on and off for both network and device data, as it is obvious to try choosing from a finite number of identified and predictable configurations.

8. Regarding claim 10, Worrall in view of Sorhag and Yanacek further show wherein means for inserting received device data into the network cable without disrupting the flow of data therein comprises an Ethernet switch (Worrall, Fig. 1(c)).

9. Regarding claim 11, Worrall in view of Sorhag and Yanacek further show wherein means for inserting received device data into the network cable without disrupting the

flow of data therein comprises an integrated circuit (Sorhaug, col. 2 lines 55 – 56, col. 3 lines 45- 47).

10. Regarding claim 12, Worrall in view of Sorhaug and Yanacek further show wherein the integrated circuit comprises a field programmable gate array (Worrall, Fig. 4).

11. Regarding claim 13, Worrall in view of Sorhaug and Yanacek further show wherein means for selecting one of the plurality of modes in which the first and second tap ports may operate comprises: a management port configured to selectively connect to a remote computer; and an integrated circuit configured to receive management data from the management port to at least indirectly enable or disable the ability of the first and second tap port to receive at least one of network data and device data (Yanacek, Figs. 2, 10A – 10C).

12. Regarding claim 15, Worrall in view of Sorhaug and Yanacek further show a network tap that permits an attached device to communicate with a node of a network, the node of the network communicating with a network cable transmitting network data thereon, the network cable having a first segment and a second segment, the network tap comprising:

- a first tap port configured to receive a copy of network data obtained from the network cable (Worrall, Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]);

- a second tap port configured to receive a copy of network data obtained from the network cable, wherein the attached device can be selectively connected to at least one of the first tap port and second tap port (Worrall, Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]), wherein at least one of the first tap port and second tap port is configured

to receive device data from the attached device (Sorhaug, Fig. 2, col. 2 lines 5 – 65), and wherein the first tap port and second tap port are configured to operate in a plurality of modes, each mode being defined by enabling or disabling the ability of the first tap port and second tap port to receive network data and device data (Yanacek, Fig. 2, 10A-10C);

a routing node that is in communication with the first tap port and second tap port, the routing node being configured to pass network data from the network cable to at least one of the first tap port and the second tap port and to pass device data from at least one of the first tap port and second tap port to the network cable (Sorhaug, col. 3 line 10 – col. 4 line 45); and

an integrated circuit (Sorhaug, col. 2 lines 55-56, col. 3 lines 45-47) configured to select the mode in which the first tap port and second tap port operate (Yanacek, Figs. 2, 10A – 10C).

13. Regarding claims 16, 17 and 19 – 24, Worrall in view of Sorhaug and Yanacek further show wherein the first and second tap ports are capable of operating in a plurality of modes, each mode being defined by enabling or disabling the ability of the first and second tap ports to receive data (Yanacek Fig. 2, 10A – 10C), including network and device data (Worrall, Figs. 1a-1c, 3a-3c; Sorhaug, Fig. 2 and col. 2 lines 5 – 65).

Worrall in view of Sorhaug and Yanacek thus disclose enabling or disabling the ability for each of the tap ports to receive network and device data.



It would have been obvious to one of ordinary skill in the art at the time of the invention to experiment and try the various permutations of on and off for both network and device data, as it is obvious to try choosing from a finite number of identified and predictable configurations.

14. Regarding claim 26, Worrall in view of Sorhaug and Yanacek further show a network tap that permits an attached device to communicate with a node of a network, the node of the network communicating with a network cable transmitting network data thereon, the network tap comprising: a first network port configured to transmit or receive network data; a second network port configured to transmit or receive network data; a first tap port configured to receive a copy of at least some of the network data (Worrall, Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]);

a second tap port configured to receive a copy of at least some of the network data (Worrall, Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]),

wherein an attached device can be selectively connected to at least one of the first tap port and second tap port (Sorhaug, Fig. 2, col. 2 lines 5 – 65),

wherein at least one of the first tap port and second tap port is configured to receive device data from the attached device (Sorhaug, Fig. 2, col. 2 lines 5 – 65), and

wherein the first tap port and second tap port are configured to operate in a plurality of modes, each mode being defined by enabling or disabling the ability of the first tap port and second tap port to receive network data and device data (Yanacek, Fig. 2, 10A-10C); and

a first switch (Worrall, Fig. 1(c)) that is in communication with the first network port and the second network port and with the first tap port and second tap port, the switch being configured to pass network data between the first network port and the second network port and transmit device data from one of the first tap port and second tap port to one of the first network port and second network port (Sorhaug, col. 3 line 10 – col. 4 line 45).

15. Regarding claim 27, Worrall in view of Sorhaug and Yanacek further show utilizing a switch that is in communication with the first network port and the second network port and with the first tap port and the second tap port, the switch being configured to combined network data from the first network port and second network port and transmit the combined network data to one of the first tap port and second tap port (Worrall, Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]).

16. Regarding claim 29, Worrall in view of Sorhaug and Yanacek further show an integrated circuit configured to select the mode in which the first tap port and the second tap port operate (Sorhaug, col. 2 lines 55 – 56; col. 3 line 10 – col. 4 line 45)

17. Regarding claim 30, Worrall in view of Sorhaug and Yanacek further show wherein the integrated circuit comprises a Field Programmable Gate Array (Worrall, Fig. 4).

18. Regarding claim 31, Worrall in view of Sorhaug and Yanacek further show a management port configured to transmit management data to the integrated circuit, the management port being configured to be selectively connected to a remote computer (Yanacek, Fig. 2, 10A-10C).

19. Claim 14 is rejected under 35 U.S.C. 103(a) as being unpatentable in view of Worarall in view of Sorhaug and Yanacek as applied to claims 1 and 13 above, further in view of Bouthillier et al. (6,092,724), hereafter Bouthillier.

Worrall in view of Sorhaug and Yanacek enable configuring a network tap to operate in one of a plurality of modes (Yanacek, Figs. 2, 10A – 10C).

Worrall in view of Sorhaug and Yanacek do not show where this mode selection is done via one or more manual switches on the network tap.

Bouthillier shows a manual switch for changing the configuration and operating mode of a network device (Abstract, Fig. 1).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall in view of Sorhaug and Yanacek with that of Bouthillier to enable the use of manual switches to configure the electronic device as manual switches are well-understood, easy to operate and reliable.

20. Claim 18 is rejected under 35 U.S.C. 103(a) as being unpatentable over Worarall in view of Sorhaug and Yanacek as applied to claim 15 and 17 above, and further in view of Bunker et al. (US 2003/0056116 A1), hereafter Bunker, further in view of Chinnock et al. (5,426,427), hereafter Chinnock.

Worarall in view of Sorhaug and Yanacek show claims 15 and 17.

Worarall in view of Sorhaug and Yanacek do not show where the attached device is an intrusion detection system; and the device data comprises a kill packet from the intrusion detection system, the routing node being configured for transmitting the kill packet via the network cable to a firewall.

Bunker shows an intrusion detection system and where the intrusion detection system can block access from particular devices ([0009-0010,0150,0312-0313]).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worarall in view of Sorhaug and Yanacek with that of Bunker as it is a combination of prior art elements according to known methods in order to yield predictable results.

Worarall in view of Sorhaug, Yanacek and Bunker do not show where said intrusion detection system utilizes a kill packet.

Chinnock shows a kill packet (col. 12 lines 1 – 25).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worarall in view of Sorhaug, Yanacek and Bunker with that of Chinnock as it is a combination of prior art elements according to known methods in order to yield predictable results.

21. Claim 25 is rejected under 35 U.S.C. 103(a) as being unpatentable over Worarall in view of Sorhaug and Yanacek as applied to claim 16 above, and further in view of Pontis et al. (US 2004/0007526 A1), hereafter Pontis.

Worarall in view of Sorhaug and Yanacek show a first multiplexer in communication with the first tap port (Yanacek, Fig. 2, 10A-10c); and a second multiplexer in communication with the second tap port (Yanacek, Fig. 2, 10A-10C), an integrated circuit (Worrall, [0024-0026]), as well as communicating with taps in order to configure them (Yanacek, Fig. 2, 10A-10C).

Worarall in view of Sorhaug and Yanacek do not show where said integrated circuit controls the first multiplexer and second multiplexer to select the mode in which the first tap port and second tap port operate.

Pontis shows a Field Programmable Gate Array (FPGA), which is inherently a type of integrated circuit, controlling a multiplexer's mode ([0075]), thus showing where said integrated circuit controls the first multiplexer and second multiplexer to select the mode in which the first tap port and second tap port operate.

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worarall in view of Sorhaug and Yanacek with that of Pontis as it involves use of known techniques (using integrated circuits to control multiplexers) to yield predictable results.

22. Claim 28 is rejected under 35 U.S.C. 103(a) as being unpatentable over Worarall in view of Sorhaug and Yanacek as applied to claim 27 above, and further in view of NetOptics (4x1 GigaBit Tap).

Worarall in view of Sorhaug and Yanacek show tap ports receiving copies of network data, and utilizing switches for duplicating combined network data and transmitting said duplicated combined data (Worarall; Abstract, Figs. 1A-1C, Figs 4 and 5, [0023-0029]; Sorhaug, col. 2 lines 1 – 22, col. 2 lines 40 – 65, col. 3 lines 10 – 45).

Worarall in view of Sorhaug and Yanacek do not explicitly show a third and a fourth tap port.

NetOptics shows a third and a fourth tap port. (pgs. 1 – 3).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall in view of Sorhaung and Yanacek with that of NetOptics in order to allow for the connection of more devices, enabling more detailed network monitoring as well as more possible monitoring configurations.

23. Claims 32 and 33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Worrall in view of Sorhaung and Yanacek as applied to claim 26 above, further in view Tomonaga et al. (5,610,913), hereafter Tomonaga and of Gromov (US 6,975,209 B2).

24. Regarding claim 32, Worrall in view of Sorhaung and Yanacek show claim 26.

Worrall in view of Sorhaung and Yanacek do not show claim 26 further comprising a first communication line from the first network port to the first switch and a second communication line from the second network port to the first switch, each of the first communication line and the second communication line including a fan out buffer that propagates the network data to the switch and propagates a copy of the network data to the first tap port and second tap port.

Tomonaga shows where multiple inputs are sent into a switch, and then a multiplex/demultiplexer unit, which comprises a fan out buffer memory (Figs. 46 and 47).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall in view of Sorhaug and NetOptics with that of Tomonaga in order to increase the number of devices and users that a network can accommodate and support (Tomonaga, col. 3 lines 57 – 67).

Worrall in view of Sorhaung, Yanacek and Tomonaga thus show a first communication line from the first network port to the first switch and a second communication line from the second network port to the first switch, each of the first communication line and the second communication line including a fan out buffer that propagates the network data to the switch and propagates a copy of the network data to the first tap port and second tap port.

Worrall in view of Sorhaung, Yanacek and Tomonaga do not show a relay for circumventing the first switch in the event of loss of power at the network tap and a transformer.

Gromov shows a relay for circumventing the first switch in the event of loss of power at the network tap and a transformer (col. 7 lines 22 – 26, Figs. 2 – 4).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the disclosure of Worrall in view of Sorhaung, Yanacek and Tomonaga with that of Gromov as it is combining prior art elements to yield predictable results.

25. Regarding claim 33, Worrall in view of Sorhaung, Yanacek, Tomonaga and Gromov show comprising a third communication line for transmitting device data from one of the first tap port and second tap port to the first switch, the third communication line including: a transformer (Gromov, Figs. 2 – 4, col. 7 lines 22 – 67); a physical layer device (Worrall, [0024-0025], Fig. 4; Sorhaug, Fig. 2, col. 1 line 65 – col. 2 line 5); and a multiplexer (Worrall, Fig. 4).


**Conclusion**

Any inquiry concerning this communication or earlier communications from the examiner should be directed to John M. Frink whose telephone number is (571) 272-9686. The examiner can normally be reached on M-F 7:30AM - 5:00PM EST; off alternate Fridays.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Andrew Caldwell can be reached on (571)272-3868. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

John Frink  
(571) 272-9686

  
ANDREW CALDWELL  
SUPERVISORY PATENT EXAMINER